

Dräger 9 liter AB composite foam extinguisher (stored pressure)

The revolution in portable fire extinguishers: Composite extinguishers are the latest development in the quest for durable corrosion resistant and low maintenance extinguishers. The extinguishers have EN3, CE and MED certification and a lifetime of 20 years. Another unique feature: the extinguishing medium in these units needs to be replaced every 10 years, as per manufacturer specifications.



General description

The red outer HDPE mantle houses a pressure vessel which is manufactured out of HDPE. The valve is supplied in nickel plated brass. Hose clips, squeeze for action handle and carrying handle are supplied in stainless steel. Due to these material and construction choices replacement of the extinguisher caused by corrosion, scratches and dents belong to the past. Resulting into lower lifetime costs. In addition the extinguisher will remain in good condition, offering greater reliability for the user when being deployed in firefighting tasks. These extinguishers offer recyclability, reducing waste output at the end of its service life.

AB foam

AB foam is suitable for fire extinguishing of substances in fire class A (containing carbons) and fire class B (flammable liquids). An additional feature is that the foam is not conductive to electricity. The foam can be used to a maximum voltage of 1000 V and at a distance of at least 1 meter.

Applications

These extinguishers are extremely suitable for harsh (outdoor, saline) conditions as found on offshore installations, marine application and moist (production) spaces.

Features

- 10 year manufacturer guarantee
- replacement of foam once every 10 years
- durable and corrosion resistant
- reliable and ultra-strong composite material
- 100% UV resistant
- ± 15% lighter than conventional extinguishers
- cost reducing
- better overview of cost control
- environmentally friendly
- recyclable product

TECHNICAL SPECIFICATIONS

Manufacturer / Model	Britannia / P50-9F
Extinguisher	Portable foam fire extinguisher
Type	Stored pressure operated
Capacity	9 liter
Fire class / Rating	34A/233B
Propellant gas	Nitrogen
Working pressure	12 bar
Suitable for electrical equipment	Up to 1000 Volt
Extinguishing agent	Foam
Temperature range	+5°C to +60°C
Color	Red (RAL3000)
Approvals	EN3, MED, CE, Rijkskeurmerk 2212